



WS-400 Series

Wireless Microphone Systems



Powerful set of features combined with exceptional performance and cost efficiency

Your *ideal choice* of **Wireless Microphone Systems**

Product Features

- Available in dual channel and single channel models
- Handheld Microphone and beltpack provides up to 10 hours continuous usage with the use of only 1 x AA battery ensuring long term cost efficiency
- Long operating range of approx. 100 m (line of sight)
- IR Sync
- Single Channel: Selectable Up to 4 simultaneous channels
* depending on region
- Dual Channel: Selectable Up to 16 simultaneous channels
* depending on region

Dual Channel Wireless Microphone System

WS-402

WS-422

WS-432



Single Channel Wireless Microphone System

WS-420

WS-430





Receiver (Dual Channel)

- Selectable up to 16 simultaneous channels
- Usable frequencies scanning and vacant channel search function
- Compact and stylish hardware
- Numerical LED display
- Indication of transmitter's battery life
- IR Sync



Receiver (Single Channel)

- Selectable up to 4 simultaneous channels
- Compact and stylish hardware
- Numerical LED display
- Fully synthesised PLL quartz tuning technology
- Indication of transmitter's battery life
- IR Sync



Handheld Microphone

- 1 AA battery provides up to 10 hours of continuous use
- Numerical LED display
- Battery life indicator

Beltpack Transmitter with Lavalier

- 1 AA battery provides up to 10 hours of continuous use
- MIC/Instrument switch
- Numerical LED display
- Adjustable sensitivity
- 3.5mm Screw Jack
- Battery life indicator
- Detachable antenna for maintenance



Dual Channel Wireless Microphone System

WS-402



WS-422



WS-432



Single Channel Wireless Microphone System

WS-420



WS-430



Specifications

Microphones	Handheld Microphone	Wireless Transmitter
Microphone unit	Dynamic with cardioid pattern	Back Electret Condenser, Omni-directional
RF Carrier Power	10 mW	
Audio Frequency Response	80 Hz - 15 kHz	50 Hz - 15 kHz
Audio input Level	140 dB SPL (maximum)	-6 dBV (maximum), mic gain 0dB
Battery Life	approx. 10 hours	
Power Supply	1 AA size alkaline battery, 1.5 V	
Finish	Resin, coating	
Dimensions	250 x ø55 mm	62 (W) x 100 (H) x 25 (D) mm (with clip)
Weight	245 g (with battery)	85 g (with battery)

Receivers	Single Channel	Dual Channel
Diversity Reception	AC mains (supplied AC-DC adapter must be used)	
Frequency Range	633 - 671 MHz, 803 - 806 MHz, UHF	
Sensitivity	10µV at 45 dBA S/N	
Squelch (SQ)	Tone SQ, Carrier SQ, Noise SQ	
Audio Frequency Response	50 Hz - 15 kHz	
Audio Output Level (Maximum)	Balanced (XLR socket) : -20 dBu Unbalanced (1/4" jack socket) : 10 dBu	Balanced (XLR socket) : 16 dBu Unbalanced (1/4" jack socket) : 10 dBu
Power Supply	11 - 18 VDC 300 mA	11 - 18 VDC 500 mA
Dimensions	215 (W) x 39 (H) x 102 (D) mm (excluding antenna and BNC)	210 (W) x 44 (H) x 202 (D) mm (excluding antenna)
Weight	480 g	720 g

Accessories



Rack Mounting Bracket Kit¹
MB-WT3²



Rack Mounting Bracket Kit¹
MB-WT4³



UHF Wireless Antenna
YW-4500



Antenna Distributor
WD-5800



Ear-Hook Microphone
Trantec YP-MS4E



Headset Microphone
Trantec YP-MS4H

Note:

1. Only for mounting of Dual Channel Receiver
2. For mounting of 1 unit of Dual Channel Receiver in an EIA standard equipment rack
3. For mounting of 2 units of Dual Channel Receiver, side-by-side in an EIA standard equipment rack

Applications



Conference Meetings



Auditorium Performances



Speech Presentations



Classroom Teaching



Smiles for the Public

TOA Electronics Pte Ltd

www.toa.com.sg

Specifications are subject to change without notice.
Printed in Singapore (65) 865-1219-02



Like us on Facebook
facebook.com/TOAasiapacific