

# 3" Line Array Speaker System (120W/480W, 100V) AS3120

## Features:

- ✓ Ideal for stadium and conventional center sound reinforcement system
- ✓ Indoor line array speaker system with 100V/70V transformer
- ✓ PA system line array speaker for background music and paging system
- ✓ 2-way speaker system 2×3" LF and 1.5" horn
- ✓ 120W rated power output and Max of 480W for each loudspeaker
- ✓ Flexible combination up to 4 units together
- ✓ Adjustable dispersion angle by different angle fixing up
- ✓ ABS material of years durable performance in black finish
- ✓ With 100V/70V matching transformer for Public Address use
- ✓ Hanging bracket and accessories had been included



## Specifications:

Model	AS3120
Description	3" Compact Line Array Speaker System
Power Output	Continuous pink noise: 120W, Continuous program: 480W
Line Input	100V or 70V
Sensitivity (1 W, 1 m)	91dB
Frequency Response	80-18kHz (±3dB)
Crossover Frequency	2.5kHz
Directivity Angle	Horizontal: 90 ° (-6dB); Vertical: 10 ° (-6dB)
Max SPL	103dB continuous; 106dB peak
Speaker	2-way speaker system 2×3" LF and 1.5" horn
Finish	Enclosure: Polypropylene, black
	Punched net: Surface-treated steel plate, black
Dimensions	250(W) × 470 (H) × 163 (D) mm
Weight	11.7kg
Mounting Bracket	Adjustable direction hanging bracket and accessories are included

## Frequency Response & SPL Diagrams:

