

# PA 100V Driver Unit (15W-30W-50W) DU-50



## Feature:

- ✓ Combination range PA driver units with transformer for optional reflex horn
- ✓ Well match with reflex horn to combine into public address (PA) horn speaker
- ✓ Transformer power output of 15W-30W-50W at 100V
- ✓ Long distance dispersion with high SPL and crisp penetrating voice
- ✓ Voice coil precision-wound on an aluminum bobbin for efficient heat dissipation
- ✓ Exactly well-matched with reflex horn with IP66 water and dust proof
- ✓ Standard 1-3/8" threaded throat well match the optional reflex horn
- ✓ Wide range temp durable from -30°C to 70°C
- ✓ Quick installation design

## Specification:

<b>Model</b>	<b>DU-50</b>
<b>Description</b>	PA 100V Driver Unit
<b>Transformer Tap</b>	15W-30W-50W
<b>Frequency Response</b>	300-6kHz
<b>SPL(1W/1m)</b>	107dB
<b>Waterproof Rate</b>	IP66
<b>Working Temp</b>	-30°C to 70°C
<b>Material</b>	Aluminum bobbin and ABS flange in grey RAL7042
<b>Throat Coupling</b>	Universal 1-3/8"
<b>Dimension</b>	138(D)×145(H)mm