

# IP Network Remote Microphone (Touch Screen)

## IP-600TM

### Feature:

- ✓ Touch screen IP remote microphone, with exquisite appetite, elegant craft and modern design.
- ✓ Full duplex two way communication between different remote microphones.
- ✓ Embed PC technology, built-in DSP & high speed industrial chip to ensure start time less than 1 second.
- ✓ With 7 inch LCD user-friendly human-machine interface.
- ✓ With touch screen control and paging to any zone.
- ✓ Several paging capacity: zone paging, group paging, all zone paging, two way intercom.
- ✓ Built-in 3W full-range monitor speakers with clear voice restoration and no echo noise.
- ✓ With USB input to broadcast pre-recorded voice message to different zones.
- ✓ Enable to transmit local sources to be broadcasted over network.
- ✓ Within one microphone input and one line input and one line output for sound system.
- ✓ 12V DC power supply, the power adapter is included in the packaging.



### Specification:

<b>Model</b>	<b>IP-600TM</b>
<b>Description</b>	<b>IP Network Remote Microphone (Touch Screen)</b>
Communication Protocol	TCP/IP, UDP, IGMP, ARP, UDP
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transmission Speed	10M/100Mbps
Frequency Response	20Hz~16KHz (+1dB, -3dB)
T.H.D.	≤0.3%
S/N Ratio	>70dB
Connector	One RJ45 port, one line input, one line output, one mic input, one USB input
Working temp	-5 °C ~ +40 °C
Humidity	10% ~ 90%
Power Consumption	≤10W
Power Supply	DC 12V
Dimensions	250x163x42mm
Weight	2.2Kg

### System Connection:

