

4 Channel IP Network Pre-Amplifier IP-604NA

Feature:

- ✓ The four channel IP network pre amplifier.
- ✓ The IP network pre-amplifier with four separate decoders.
- ✓ Four IP program simultaneously broadcast without interference.
- ✓ It is high capacity but cost-effective multiple room network sound system.
- ✓ The system could be set up over existing network, non dedicated network is needed.
- ✓ System capacity of 6000 IP decoder online simultaneously.
- ✓ Eight zone contact outputs for zone status monitoring.
- ✓ Support LAN/WAN and Internet network.
- ✓ Network data delay of less than 30 milliseconds.
- ✓ Remote volume control and program edit from server.
- ✓ Remote paging system by work with IP-600TM IP remote microphone.



Specification:

Model	IP-604NA
Description	Four Channel IP Network Pre-Amplifier
Power Supply	AC230V, 50-60Hz
Power Consumption	30W
Network Protocol	TCP, UDP, ARP, ICMP, IGMP
Network Speed	10/100Mbps
Audio Format	Mp2, Mp3, PCM, ADPCM
Audio Sampling	8KHz-44.1KHz, 16 bits, 8K-320Kbps
S/N Ratio	≥90dB
Frequency Response	20Hz-20KHz
Data Delay	30 milliseconds
Connector	four aux inputs, four aux outputs, , four RJ45 inputs, one 100V power input
Working Temperature	-5°C to +40°C
Humidity	10% ~ 90%
Dimensions	484×365×88mm
Weight	6.8kg

Connection Diagram:

